



TECHNICAL DATA

| | |
|-----------------------------------|-------------|
| Item no. | 1006946 |
| Number of different light outlets | 1 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 250 mA |
| Safety class | III |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 730 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Risk Group | 1 |
| Length | 12.5 cm |
| Diameter | 6 cm |
| Net weight | 0.55 kg |
| Gross weight | 0.589 kg |
| Shape of cut-out | round |
| Installation length | 15 cm |

Light Source

| | |
|--------|---|
| 791815 |  |
|--------|---|

| | |
|-----------------------|--------|
| Installation diameter | 8.8 cm |
|-----------------------|--------|

Accessories

| | |
|---------|-------------------------------------|
| 1004055 | LED driver , 6.5-10W 250mA PHASE |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004789 | NUMINOS® S , diffuser Wabe |