




M-POL S Polehead 360°

low-glare, lamp head, anthracite, 10W, 750lm, 2700K, CRI80

M-POL means the SLV outdoor family whose members bear individual lamp heads. The M-POL S Polehead also leads the way here: the low-glare and 2700K warm-white beam of light illuminates the path, which avoids light pollution and contributes to a dark sky. Thanks to its IP65 rating, the lamp heads are wind and weather-proof and the IK10 protection class even means they are protected against heavy impact. Simply perfect for illuminating outdoor commercial areas in high quality.



TECHNICAL DATA

Item no.	1007232
IP Code	IP 65
Impact resistance class	IK 10
Impact resistance	20 Joule
Assembly details	Ground with Acc.
Number of through-wires	17
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Wattage	10 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0,54
Number of luminaires at LS B16A	97
Number of luminaires at LS C16A	121
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Lumen	750 lm
Colour temperature	2700 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L80B50
Service life	50000 h

Light Source

	
--	---

Accessories

1006381	M-POL 90 Pole , Bollard, anthracite, 83.4cm
228726	T-CONNECTION BOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68
1006379	M-POL 30 Pole , Bollard, anthracite, 23.4cm
1006380	M-POL 60 Pole , Bollard, anthracite, 53.4cm
1006382	M-POL ground anchor , stainless steel

Risk Group	1
Height	16.4 cm
Diameter	12.09 cm
Net weight	1.05 kg
Gross weight	1.124 kg
BIG WHITE Page	614