




M-POL S Polehead 360°

low-glare, lamp head, anthracite, 10W, 750lm, 2700K, CRI80, DALI

M-POL means the SLV outdoor family whose members bear individual lamp heads. The M-POL S Polehead also leads the way here: the DALI-dimmable, low-glare and 2700K warm-white beam of light illuminates the path, which avoids light pollution and contributes to a dark sky. Thanks to its IP65 rating, the lamp heads are wind and weather-proof and the IK10 protection class even means they are protected against heavy impact. Simply perfect for illuminating outdoor commercial areas in high quality.



TECHNICAL DATA

| | |
|---------------------------------|-------------------|
| Item no. | 1007233 |
| IP Code | IP 65 |
| Impact resistance class | IK 10 |
| Impact resistance | 20 Joule |
| Assembly details | Ground with Acc. |
| Dimmable | Yes |
| Dimming technology | DALI |
| Number of through-wires | 20 |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Wattage | 10 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Operating efficiency (LOR) | 0,54 |
| Rated standby power | 0.5 W |
| Number of luminaires at LS B16A | 80 |
| Number of luminaires at LS C16A | 100 |
| Level of inrush current | 15 A |
| Duration of inrush current | 100 µs |
| Lumen | 750 lm |
| Colour temperature | 2700 Kelvin |
| Color | anthracite |

Light Source

| | |
|--|---|
| |  |
|--|---|

Accessories

| | |
|---------|---|
| 1006381 | M-POL 90 Pole , Bollard, anthracite, 83.4cm |
| 1006453 | Connection box , 5-pin, IP68, black, DALI |
| 1006379 | M-POL 30 Pole , Bollard, anthracite, 23.4cm |
| 1006380 | M-POL 60 Pole , Bollard, anthracite, 53.4cm |
| 1006382 | M-POL ground anchor , stainless steel |
| 228725 | CONNECTION BOX , 5-pin, IP68 |

| | |
|----------------|----------|
| CRI | 80 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 16.4 cm |
| Diameter | 12.09 cm |
| Net weight | 1.05 kg |
| Gross weight | 1.124 kg |
| BIG WHITE Page | 614 |