




## M-POL S Polehead 180°

low-glare, lamp head, anthracite, 10W, 750lm, 2700K, CRI80

M-POL means the SLV outdoor family whose members bear individual lamp heads. The M-POL S Polehead also leads the way here: the low-glare and 2700K warm-white beam of light illuminates the path, which avoids light pollution and contributes to a dark sky. Thanks to its IP65 rating, the lamp heads are wind and weather-proof and the IK10 protection class even means they are protected against heavy impact. Simply perfect for illuminating outdoor commercial areas in high quality.



## TECHNICAL DATA

Item no.	1007234
IP Code	IP 65
Impact resistance class	IK 10
Impact resistance	20 Joule
Assembly details	Ground with Acc.
Number of through-wires	17
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Wattage	10 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0,503
Number of luminaires at LS B16A	97
Number of luminaires at LS C16A	121
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Lumen	700 lm
Colour temperature	2700 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L80B50
Service life	50000 h

## Light Source

	
--	---

### Accessories

1006381	M-POL 90 Pole , Bollard, anthracite, 83.4cm
228726	T-CONNECTION BOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68
1006379	M-POL 30 Pole , Bollard, anthracite, 23.4cm
1006380	M-POL 60 Pole , Bollard, anthracite, 53.4cm
1006382	M-POL ground anchor , stainless steel

Risk Group	1
Height	16.4 cm
Diameter	12.09 cm
Net weight	1.05 kg
Gross weight	1.124 kg
BIG WHITE Page	615