




I-RING

free-standing lamp, 9.2W, 3000K, anthracite

Indirect lighting in an organic ring shape summed up: the new I-RING floor light creates flexible and warm-white (3000K) accented lighting in upmarket outdoor areas thanks to its pivoting and rotatable lamp head. It also prevents light pollution as far as possible. The anthracite-coloured outdoor light is optimally protected thanks to its IP65 rating and features an exceptionally long lifespan of 50,000 hours. A well-rounded lighting experience.



TECHNICAL DATA

Item no.	1007237
Rotating or tilting	Rotary bar and tiltable
IP Code	IP 65
Impact resistance class	IK 05
Assembly	Surface
Assembly details	Ground
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	9.2 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Operating efficiency (LOR)	0,54
Number of luminaires at LS B16A	50
Number of luminaires at LS C16A	80
Level of inrush current	12 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.03
Lumen	670 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80

Light Source

1807467	
---------	---

Accessories

228753	SCREW SET , stainless steel, M8, incl. cap nuts, plugs and washers
--------	--

LXXBXX data	L70B50
Service life	50000 h
Risk Group	0
Height	65 cm
Diameter	24 cm
Net weight	2.17 kg
Gross weight	2.322 kg
BIG WHITE Page	613