


MEDO® 90

ceiling-mounted light, round, 2700/3000/4000K, 79W, trailing-edge phase, 110°, white

The new MEDO® sets standards and impresses with a longer service life, better energy efficiency and a higher indirect light component. The improved protection code IP50 and an outstanding CRI>90 colour reproduction index ensure exceptional quality. Three elegant casing colours and a CCT switch that enables you to choose between 2700 K, 3000 K and 4000 K lets you personalise your lighting situation. And thanks to EasyBase, installation is as simple as it is fast.



TECHNICAL DATA

| | |
|-----------------------------------|----------------------------|
| Item no. | 1007326 |
| Number of different light outlets | 2 |
| IP Code | IP 50 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Ceiling, Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 1000 mA |
| Safety class | I |
| Wattage | 79 W |
| Ambient temperature | 25 °C |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Number of luminaires at LS B16A | 27 |
| Number of luminaires at LS C16A | 33 |
| Level of inrush current | 12 A |
| Duration of inrush current | 45 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 8300/8700/9350 lm |

Light Source

| | |
|--|---|
| |  |
|--|---|

Accessories

| | |
|---------|---|
| 1001952 | MEDO 5m suspension , black |
| 1001950 | MEDO 5m suspension , white |
| 135250 | SUSPENSION SET , for MEDO round pendant, round, black, 5-wire |
| 1001951 | MEDO 5m suspension , silver-grey |
| 135251 | SUSPENSION SET , for MEDO round pendant, round, white, 5-wire |
| 135254 | SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire |

| | |
|--------------------|-----------------------|
| Colour temperature | 2700/3000/4000 Kelvin |
| Beam angle | 110 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L70B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 9.2 cm |
| Diameter | 90 cm |
| Net weight | 9 kg |
| Gross weight | 9.63 kg |
| BIG WHITE Page | 161 |