




## NEW TRIA® 68

recessed ceiling light, 3000K, 38°, IP 20, round, black

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are also available as a complete set. The integrated LED MODULE, which is available with different light colours (2700K/3000K) and beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light. In black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68mm mounting ring supplied, the downlights can also be installed quickly and simply.



## TECHNICAL DATA

Item no.	1007390
Rotating or tilting	Tilttable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	200 mA
Safety class	II
Wattage	8.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	149
Level of inrush current	3 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.4
Lumen	750 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black

## Light Source

869620	
--------	---

<b>CRI</b>	90
<b>LXXBXX data</b>	L80B10
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Height</b>	4 cm
<b>Diameter</b>	8.2 cm
<b>Net weight</b>	0.18 kg
<b>Gross weight</b>	0.193 kg
<b>Shape of cut-out</b>	round
<b>Installation depth</b>	4 cm
<b>Installation diameter</b>	6.8 cm
<b>BIG WHITE Page</b>	134