




WORKLIGHT PRO

free-standing lamp, 150W, 4000K, Touch, grey



The new WORKLIGHT PRO stands for high performance in the workplace: the free-standing lamp is optimally designed in line with the latest DIN EN 12464:2021 standard. Its glare-free ($UGR < 14$) luminous efficiency of 130 lm/W, a colour temperature of 4000K and improved, indirect light output offers everything you need for an ergonomic working environment. Dimmability, daylight control, a motion sensor and long lifespan (L80/B10 50,000h) also help to make the free-standing office lamp what it is: a true SLV colleague that assists with productivity.



TECHNICAL DATA

Item no.	1007467
Number of different light outlets	2
IP Code	IP 20
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Mobile
Dimmable	Yes
Dimming technology	Touch
Primary nominal voltage	200-240V ~50/60Hz
Secondary power / voltage	48 V
Safety class	I
Wattage	150 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	3
Number of luminaires at LS C16A	5
Level of inrush current	72 A
Duration of inrush current	410 μ s
Stroboscopic effect (SVM)	0.4
Lumen	20000 lm
Colour temperature	4000 Kelvin
Beam angle	75 °

Light Source

1807475	
1807479	

Color	grey
CRI	80
UGR \leq	16
LXXBXX data	L80B10
Service life	50000 h
Risk Group	0
Length	163.4 cm
Width	24 cm
Height	200 cm
Net weight	20.7 kg
Gross weight	22.149 kg
BIG WHITE Page	444