




HIGHBAY C

DALI 400 200W 840 IP65

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the HIGHBAY product family, which is available in two sizes (340 and 400 mm diameter) and also as a DALI version with the HIGHBAY C 400. They impress with their efficiency of >175 lm/W and the two luminaires without DALI control can also be supplemented with sensors and a CASAMBI module for intelligent lighting control.



TECHNICAL DATA

Item no.	1008527
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Surface
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	880 mA
Safety class	I
Wattage	200 W
Minimum ambient temperature	-30 °C
Maximum ambient temperature	50 °C
Number of luminaires at LS B16A	5
Number of luminaires at LS C16A	9
Level of inrush current	130 A
Duration of inrush current	200 µs
Lumen	35000 lm
Colour temperature	4000 Kelvin
Color	black
CRI	80

UGR ≤	22
Service life	50000 h
Risk Group	1
Height	11.8 cm
Diameter	40 cm
Net weight	3.3 kg
Gross weight	4.7 kg

Accessories

1008528	HIGHBAY C , U-bracket
1008530	Highbay C , 400 PC re- flector