


## ORDI II

**POLE 70, outdoor free-standing lamp, angular, 2200/3000 K, IP65, black**

The successful ORDI II product family is being extended to include robust, high-output bollard lights - specially developed for private outdoor areas. With their clear, angular design and uniform light distribution, the lights blend seamlessly into modern outdoor spaces. A CCT switch allows you to choose between warm white 3,000 K and insect-friendly 2,200 K light - for atmospheric lighting with respect for nature. The sea and salt air resistant surface and the protection class IP65 make ORDI II ideal for permanently demanding outdoor conditions. Available in two heights (45 cm and 70 cm), ORDI II also offers a sensor version. This is equipped with a primary/replica function: one light takes over the control, others can be automatically switched on via through-wiring - perfect for paths, driveways or entrance areas.



## TECHNICAL DATA

<b>Item no.</b>	1008726
<b>IP Code</b>	IP65
<b>Impact resistance class</b>	IK 07
<b>Impact resistance</b>	2 Joule
<b>Assembly</b>	Surface
<b>Assembly details</b>	Ground
<b>Dimmable</b>	Yes
<b>Dimming technology</b>	Leading edge,trailing edge
<b>Number of through-wires</b>	150
<b>Primary nominal voltage</b>	220-240V ~50/60 Hz
<b>Secondary power / voltage</b>	240 mA
<b>Safety class</b>	I
<b>Wattage</b>	9.5 W
<b>Minimum ambient temperature</b>	-25 °C
<b>Maximum ambient temperature</b>	45 °C
<b>Number of luminaires at LS B16A</b>	210
<b>Number of luminaires at LS C16A</b>	210
<b>Level of inrush current</b>	4.1 A
<b>Duration of inrush current</b>	81 µs
<b>Temperature at glass (light emission)</b>	55 °C
<b>Lumen</b>	700 / 850 lm
<b>Colour temperature</b>	2200/3000 Kelvin

## Light Source

2261485		<table border="1"><tr><td><b>Color</b></td><td>black</td></tr><tr><td><b>CRI</b></td><td>80</td></tr><tr><td><b>Service life</b></td><td>50000 h</td></tr><tr><td><b>Risk Group</b></td><td>0</td></tr><tr><td><b>Width</b></td><td>18 cm</td></tr><tr><td><b>Height</b></td><td>70 cm</td></tr><tr><td><b>Depth</b></td><td>11.7 cm</td></tr><tr><td><b>Net weight</b></td><td>3.06 kg</td></tr><tr><td><b>Gross weight</b></td><td>3.63 kg</td></tr><tr><td><b>BIG WHITE Page</b></td><td>795</td></tr></table>	<b>Color</b>	black	<b>CRI</b>	80	<b>Service life</b>	50000 h	<b>Risk Group</b>	0	<b>Width</b>	18 cm	<b>Height</b>	70 cm	<b>Depth</b>	11.7 cm	<b>Net weight</b>	3.06 kg	<b>Gross weight</b>	3.63 kg	<b>BIG WHITE Page</b>	795
<b>Color</b>	black																					
<b>CRI</b>	80																					
<b>Service life</b>	50000 h																					
<b>Risk Group</b>	0																					
<b>Width</b>	18 cm																					
<b>Height</b>	70 cm																					
<b>Depth</b>	11.7 cm																					
<b>Net weight</b>	3.06 kg																					
<b>Gross weight</b>	3.63 kg																					
<b>BIG WHITE Page</b>	795																					