




TRACKSPOT C 3 Ph. 29W 940 36°

White


The TRACKSPOT C 3-phase spotlight, which is compatible with S-Track and Eutrac systems, is the ideal choice for demanding commercial projects with a moderate budget, where high efficiency and the lowest possible energy consumption are the key points of focus. With an energy efficiency of over 145 lm/W, excellent colour rendering thanks to CRI 90, and a high luminous flux of up to 4,400 lumens, the luminaire offers a lighting solution that is perfect for small and large commercial areas. Thanks to a service life of 50,000 hours (L80B50), the TRACKSPOT C also ensures long-term reliability and reduces maintenance costs. Available in different versions with 17W or 29W, beam angles of 36° or 50°, in 3,000 K and 4,000 K, the TRACKSPOT C comes in black and white versions. This flexibility enables harmonious integration into different room concepts.



TECHNICAL DATA

Item no.	1008872
Number of different light outlets	1
IP Code	IP20
Assembly details	Ceiling, Wall
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	800 mA
Safety class	II
Wattage	29 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	15
Number of luminaires at LS C16A	24
Level of inrush current	65 A
Duration of inrush current	400 µs
Lumen	4200 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
CRI	90
Service life	50000 h
Length	10.5 cm
Height	14 cm
Diameter	10 cm

Light Source

2194011		Net weight	0.72 kg
		Gross weight	0.88 kg