




## DECONA 42 CL

**PHASE, Ceiling-mounted light, Round, 3000/4000K, 23 W, White**

Discover modern design at an attractive price-performance ratio: DECONA ceiling-mounted lights are available in two different sizes and in black, white or with a golden inner ring to add a trendy colour accent. With separately available recessed frames and suspension kits, the luminaires can also be installed as recessed and pendant lights. And thanks to their IP44 protection class, they are also suitable for use in the bathroom.



## TECHNICAL DATA

|                                 |                    |
|---------------------------------|--------------------|
| Item no.                        | 1008921            |
| IP Code                         | IP44               |
| Impact resistance class         | IK 06              |
| Impact resistance               | 1 Joule            |
| Assembly                        | Surface            |
| Assembly details                | Ceiling            |
| Dimmable                        | Yes                |
| Dimming technology              | trailing edge      |
| Primary nominal voltage         | 220-240V ~50/60 Hz |
| Secondary power / voltage       | 300 mA             |
| Safety class                    | II                 |
| Wattage                         | 23 W               |
| Minimum ambient temperature     | -20 °C             |
| Maximum ambient temperature     | 45 °C              |
| Number of luminaires at LS B16A | 75                 |
| Number of luminaires at LS C16A | 75                 |
| Level of inrush current         | 4.2 A              |
| Duration of inrush current      | 62.8 µs            |
| Lumen                           | 2770/2930 lm       |
| Colour temperature              | 3000/4000 Kelvin   |
| CRI                             | 90                 |
| UGR ≤                           | 25                 |

## Light Source

|         |                                                                                   |                     |         |
|---------|-----------------------------------------------------------------------------------|---------------------|---------|
| 2254627 |  | <b>Service life</b> | 50000 h |
|         |                                                                                   | <b>Risk Group</b>   | 0       |
|         |                                                                                   | <b>Height</b>       | 5.8 cm  |
|         |                                                                                   | <b>Diameter</b>     | 42 cm   |
|         |                                                                                   | <b>Net weight</b>   | 2.31 kg |
|         |                                                                                   | <b>Gross weight</b> | 2.83 kg |