




## FIXT-IT!

48V, DALI, Round, Surface mounted track, Spot, 2700-K, 6.6 W, 36°, Gold/Black

Discover maximum variety and modern design with the new FIXT-IT! 48V spotlights for the SLV 48V track system. These decorative, direct spotlights set new standards in interior lighting and offer countless design options. The FIXT-IT! series is compatible with the deep and standard 48V mounting tracks from SLV. Thanks to UGR<11, the FIXT-IT! spotlights create a fascinating lighting effect with an almost invisible light source - ideal for sophisticated design concepts. The versions with 2,700 K or 3,000 K bring warm light and impressive energy efficiency into any room. With the Dim-to-Warm variants (2,000 K-3,000 K), the FIX-T-IT! spots offer even more possibilities, for cosy lighting moods. The spotlights also offer a sustainable lighting solution with a service life of 50,000 hours. The FIXT-IT! Spotlights are not only technically impressive, but also visually: the compact design ensures an elegant overall appearance. They are available in the timeless colour combinations black/black, white/black, gold/black, and bronze/black. Furthermore, the different designs - round or square - and the interchangeable coloured decorative inserts offer further customisation options. Experience the perfect combination of high-quality lighting and creative freedom - FI-X-IT! opens up new horizons in lighting design.



## **TECHNICAL DATA**

Item no.	1008959
Number of different light outlets	1
IP Code	IP20
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	48DC
Secondary power / voltage	175 mA
Safety class	III
Wattage	6.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	800 lm
Lumen Colour temperature	800 lm 2700 Kelvin
Colour temperature	2700 Kelvin
Colour temperature  Beam angle	2700 Kelvin 36 °
Colour temperature  Beam angle  CRI	2700 Kelvin 36 °
Colour temperature  Beam angle  CRI  UGR ≤	2700 Kelvin  36 °  90  19
Colour temperature  Beam angle  CRI  UGR ≤  Service life	2700 Kelvin  36 °  90  19  50000 h
Colour temperature  Beam angle  CRI  UGR ≤  Service life  Risk Group	2700 Kelvin  36 °  90  19  50000 h
Colour temperature  Beam angle  CRI  UGR ≤  Service life  Risk Group  Height	2700 Kelvin  36 °  90  19  50000 h  1  8.2 cm



Gross weight	0.26 kg

## **Accessories**

1008996	FIXT-IT! bronze round decorative insert
1008994	FIXT-IT! black round de- corative insert
1008995	FIXT-IT! gold round decorative insert
1008993	FIXT-IT! white round de- corative insert