


GRIP! M

Ceiling-mounted light, double, PHASE, 3000K, 28W, 42°, bronze / black

GRIP! - the striking light family for sophisticated lighting design. With its distinctive knurled front ring and many new pendant, surface-mounted and recessed options, GRIP! now offers even more options for customised lighting concepts. The honeycomb louvre insert supplied as standard reduces glare and ensures optimum visual comfort. Different colours and designs blend harmoniously into living spaces, hotels or restaurants. High-quality technology with a CRI of 90, a lifetime of 50,000 hours and easy installation make GRIP! an all-round convincing choice.



TECHNICAL DATA

Item no.	1009081
Number of different light outlets	2
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	0 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	19
Number of luminaires at LS C16A	33
Level of inrush current	12 A
Duration of inrush current	400 µs
Lumen	3040 lm
Colour temperature	3000 Kelvin
Beam angle	42 °

Light Source

2093860	
---------	---

Accessories

1008495	GRIP! M , decorative ring, gold
1008494	GRIP! M , decorative ring, nickel
1008492	GRIP! M , decorative ring, white
1008493	GRIP! M , decorative ring, black

Color	bronze/black
CRI	90
Service life	50000 h
Risk Group	1
Length	27.4 cm
Width	14.7 cm
Height	10.6 cm
Net weight	0.744 kg
Gross weight	0.956 kg