




GRIP! L

SPOT CL, double, QPAR51, ceiling-mounted light, cylindrical, 2 x max. 6 watts, black / gold

The GRIP! Size L SPOT ceiling-mounted spotlights combine contemporary design with functional lighting technology - ideal for both domestic and commercial applications. Available in single or twin versions, each with a GU10-fitting (QPAR51) socket, they provide targeted, flexible lighting directly on the ceiling. Available in four elegant finishes - bronze, gold, black and white - the spotlights blend harmoniously into a variety of interior styles. For even more design freedom, they can be combined with optional decorative rings in contemporary colours that can be changed in seconds. All GRIP! Spots are supplied with a honeycomb grid as standard - for glare-free light and optimum visual comfort. For accent light or basic lighting – GRIP! SPOT L impresses with its stylish appearance and reliability.



TECHNICAL DATA

SocketGU10Number of sockets2Tilt range90 °Horizontal rotation range340 °IP CodeIP20Impact resistance classIK 02Impact resistance0.2 JouleAssemblySurfaceAssembly detailsCeilingPrimary nominal voltage220-240V ~50/60 HzSafety classIWattage6 WColorblack/goldWidth32.5 cmHeight5.7 cmDepth9.8 cm	Item no.	1009097
Tilt range 90 ° Horizontal rotation range 340 ° IP Code IP20 Impact resistance class IK 02 Impact resistance 0.2 Joule Assembly Surface Assembly Ceiling Primary nominal voltage 220-240V ~50/60 Hz Safety class I Wattage 6 W Color black/gold Width 32.5 cm Height 5.7 cm	Socket	GU10
Horizontal rotation range IP Code IP20 Impact resistance class IK 02 Impact resistance O.2 Joule Assembly Surface Assembly details Ceiling Primary nominal voltage Safety class I Wattage Golor black/gold Width 32.5 cm Height	Number of sockets	2
IP Code Impact resistance class IK 02 Impact resistance O.2 Joule Assembly Surface Assembly details Ceiling Primary nominal voltage 220-240V ~50/60 Hz Safety class I Wattage 6 W Color black/gold Width 32.5 cm Height 5.7 cm	Tilt range	90 °
Impact resistance classIK 02Impact resistance0.2 JouleAssemblySurfaceAssembly detailsCeilingPrimary nominal voltage220-240V ~50/60 HzSafety classIWattage6 WColorblack/goldWidth32.5 cmHeight5.7 cm	Horizontal rotation range	340°
Impact resistance0.2 JouleAssemblySurfaceAssembly detailsCeilingPrimary nominal voltage220-240V ~50/60 HzSafety classIWattage6 WColorblack/goldWidth32.5 cmHeight5.7 cm	IP Code	IP20
Assembly Surface Assembly details Ceiling Primary nominal voltage 220-240V ~50/60 Hz Safety class I Wattage 6 W Color black/gold Width 32.5 cm Height 5.7 cm	Impact resistance class	IK 02
Assembly details Primary nominal voltage 220-240V ~50/60 Hz Safety class I Wattage 6 W Color black/gold Width 32.5 cm Height 5.7 cm	Impact resistance	0.2 Joule
Primary nominal voltage 220-240V ~50/60 Hz Safety class Wattage 6 W Color black/gold Width 32.5 cm Height 5.7 cm	Assembly	Surface
Safety class Wattage 6 W Color black/gold Width 32.5 cm Height 5.7 cm	Assembly details	Ceiling
Wattage 6 W Color black/gold Width 32.5 cm Height 5.7 cm	Primary nominal voltage	220-240V ~50/60 Hz
Color black/gold Width 32.5 cm Height 5.7 cm	Safety class	I
Width 32.5 cm Height 5.7 cm	Wattage	6 W
Height 5.7 cm	Color	black/gold
	Width	32.5 cm
Depth 9.8 cm	Height	5.7 cm
	Depth	9.8 cm
Net weight 0.552 kg	Net weight	0.552 kg
Gross weight 0.79 kg	Gross weight	0.79 kg



Recommended lamp

1005079	LED lightbulb QPAR51 , GU10, 3000 K, white
Accessories	
1008498	GRIP! L , decorative ring, nickel
1008497	GRIP! L , decorative ring, black
1008499	GRIP! L , decorative ring, gold
1008496	GRIP! L , decorative ring, white