


## SIGHT PANEL

3~ spot, DALI, rectangular, 4000K, 65W, 70°, black

SIGHT PANEL - the high-output spot solution for 3-phase track mounting in shops, galleries or exhibition areas. With a 70° beam angle, CRI>90 and optional DALI control, it provides precise, high-quality light exactly where it is needed. The flexible swivel mechanism allows for precise alignment and the easy installation saves time - for perfect staging of any project.



## TECHNICAL DATA

|                                 |                    |
|---------------------------------|--------------------|
| Item no.                        | 1009152            |
| IP Code                         | IP20               |
| Impact resistance class         | IK 02              |
| Impact resistance               | 0.2 Joule          |
| Assembly details                | Ceiling            |
| Dimmable                        | Yes                |
| Dimming technology              | DALI               |
| Primary nominal voltage         | 220-240V ~50/60 Hz |
| Secondary power / voltage       | 330 mA             |
| Safety class                    | I                  |
| Wattage                         | 65 W               |
| Minimum ambient temperature     | -20 °C             |
| Maximum ambient temperature     | 35 °C              |
| Number of luminaires at LS B16A | 21                 |
| Number of luminaires at LS C16A | 35                 |
| Level of inrush current         | 23 A               |
| Duration of inrush current      | 174 µs             |
| Lumen                           | 11600 lm           |
| Colour temperature              | 4000 Kelvin        |
| Beam angle                      | 70 °               |
| Color                           | black              |
| CRI                             | 90                 |

## Light Source

|  |                                                                                   |
|--|-----------------------------------------------------------------------------------|
|  |  |
|--|-----------------------------------------------------------------------------------|

|                     |         |
|---------------------|---------|
| <b>UGR ≤</b>        | 25      |
| <b>Service life</b> | 50000 h |
| <b>Length</b>       | 58 cm   |
| <b>Width</b>        | 19 cm   |
| <b>Height</b>       | 6.5 cm  |
| <b>Net weight</b>   | 2.11 kg |
| <b>Gross weight</b> | 2.47 kg |