


NUMINOS® MOVE XS

Recessed ceiling light, 2700 K, 40°, IP20, round, black

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® MOVE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1009328
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	900 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	5.3 cm
Diameter	8 cm
Net weight	0.11 kg

Light Source

2093755		Gross weight	0.22 kg
Accessories		Shape of cut-out	round
1005614	NUMINOS® XS , frosted diffuser	Installation depth	8 cm
1010126	NUMINOS® XS , reflector, copper	Installation diameter	6.8 cm
1010695	LED driver , 21W, 200 mA, DALI		
1010703	LED driver , 23W, 200 mA, DALI		
1005612	NUMINOS® XS , diffuser		
1010699	LED driver , 10W, 200 mA, PHASE		
1005615	NUMINOS® XS , black diffuser		
1010125	NUMINOS® XS , reflector, gold		
1005613	NUMINOS® XS , transparent diffuser		