


NUMINOS® MOVE XS

Recessed ceiling light, 3000 K, 55°, IP20, round, black / white

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The different downlights and spotlights make a thousand lighting design options possible. This also includes NUMINOS® MOVE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1009350 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 200 mA |
| Safety class | III |
| Wattage | 6.9 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 950 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | black/white |
| CRI | 90 |
| UGR ≤ | 25 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 5.3 cm |
| Diameter | 8 cm |
| Net weight | 0.11 kg |

Light Source

| | |
|---------|---|
| 2093745 |  |
|---------|---|

Accessories

| | |
|---------|------------------------------------|
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1010126 | NUMINOS® XS , reflector, copper |
| 1010695 | LED driver , 21W, 200 mA, DALI |
| 1010703 | LED driver , 23W, 200 mA, DALI |
| 1005612 | NUMINOS® XS , diffuser |
| 1010699 | LED driver , 10W, 200 mA, PHASE |
| 1005615 | NUMINOS® XS , black diffuser |
| 1010125 | NUMINOS® XS , reflector, gold |
| 1005613 | NUMINOS® XS , transparent diffuser |

| | |
|-----------------------|---------|
| Gross weight | 0.22 kg |
| Shape of cut-out | round |
| Installation depth | 8 cm |
| Installation diameter | 6.8 cm |