


NUMINOS® GIMBLE S

Recessed ceiling light, 3000 K, 40°, IP20, round, white

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® GIMBLE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1009410
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1050 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	7 cm
Diameter	10 cm
Net weight	0.188 kg

Light Source

2093839		Gross weight	0.288 kg
Accessories		Shape of cut-out	round
1010128	NUMINOS® S , reflector, copper	Installation depth	7 cm
1010681	NUMINOS® S , frosted diffuser	Installation diameter	9 cm
1010682	NUMINOS® S , Elliptical diffuser		
1010679	NUMINOS® S , Honey-comb diffuser		
1010695	LED driver , 21W, 200 mA, DALI		
1010703	LED driver , 23W, 200 mA, DALI		
1010699	LED driver , 10W, 200 mA, PHASE		
1010127	NUMINOS® S , reflector, gold		
1010680	NUMINOS® S , Prismatic diffuser		