


NUMINOS® M

Recessed ceiling light, 2700 K, 55°, IP20, round, black

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® DL M recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 12 watts, luminous flux of 1700 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1009601
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1700 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.22 kg
Gross weight	0.28 kg

Light Source

2093870		Shape of cut-out	round
Accessories			
1010704	LED driver , 23W, 350 mA, DALI		
1010700	LED driver , 20W, 350 mA, PHASE		
1010129	NUMINOS® M , reflector, gold		
1010683	NUMINOS® M , Honeycomb diffuser		
1010686	NUMINOS® M , Elliptical diffuser		
1010684	NUMINOS® M , Prismatic diffuser		
1010696	LED driver , 21W, 350 mA		
1010685	NUMINOS® M , frosted diffuser		
1010130	NUMINOS® M , reflector, copper		