


NUMINOS® M

Recessed ceiling light, 2700 K, 20°, IP20, round, white

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® DL M recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 12 watts, a luminous flux of 1700 lumens, a colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



TECHNICAL DATA

Item no.	1009605
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1700 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.22 kg
Gross weight	0.28 kg

Light Source

2093870		Shape of cut-out	round
Accessories			
1010704	LED driver , 23W, 350 mA, DALI		
1010700	LED driver , 20W, 350 mA, PHASE		
1010129	NUMINOS® M , reflector, gold		
1010683	NUMINOS® M , Honeycomb diffuser		
1010686	NUMINOS® M , Elliptical diffuser		
1010684	NUMINOS® M , Prismatic diffuser		
1010696	LED driver , 21W, 350 mA		
1010685	NUMINOS® M , frosted diffuser		
1010130	NUMINOS® M , reflector, copper		