


NUMINOS® MOVE M

Recessed ceiling light, 2700 K, 40°, IP20, round, black

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® MOVE DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 12 watts, a luminous flux of 1700 lumens, a colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



TECHNICAL DATA

Item no.	1009652
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1700 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	8 cm
Diameter	13.5 cm
Net weight	0.35 kg

Light Source

2093870		Gross weight	0.45 kg
Accessories			
1010704	LED driver , 23W, 350 mA, DALI	Shape of cut-out	round
1010700	LED driver , 20W, 350 mA, PHASE	Installation depth	10 cm
1010129	NUMINOS® M , reflector, gold	Installation diameter	12 cm
1010683	NUMINOS® M , Honeycomb diffuser		
1010686	NUMINOS® M , Elliptical diffuser		
1010684	NUMINOS® M , Prismatic diffuser		
1010696	LED driver , 21W, 350 mA		
1010685	NUMINOS® M , frosted diffuser		
1010130	NUMINOS® M , reflector, copper		