


## NUMINOS® MOVE M

Recessed ceiling light, 3000 K, 40°, IP20, round, black / white

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. Also with the NUMINOS® MOVE DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 12 watts, luminous flux of 1800 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1009671                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| IP Code                           | IP20                    |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 350 mA                  |
| Safety class                      | III                     |
| Wattage                           | 12 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 1800 lm                 |
| Colour temperature                | 3000 Kelvin             |
| Beam angle                        | 40 °                    |
| Color                             | black/white             |
| CRI                               | 90                      |
| UGR ≤                             | 19                      |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 8 cm                    |
| Diameter                          | 13.5 cm                 |
| Net weight                        | 0.35 kg                 |

## Light Source

|         |   |
|---------|---|
| 2093856 |  |
|---------|---|

### Accessories

|         |                                  |
|---------|----------------------------------|
| 1010704 | LED driver , 23W, 350 mA, DALI   |
| 1010700 | LED driver , 20W, 350 mA, PHASE  |
| 1010129 | NUMINOS® M , reflector, gold     |
| 1010683 | NUMINOS® M , Honey-comb diffuser |
| 1010686 | NUMINOS® M , Elliptical diffuser |
| 1010684 | NUMINOS® M , Prismatic diffuser  |
| 1010696 | LED driver , 21W, 350 mA         |
| 1010685 | NUMINOS® M , frosted diffuser    |
| 1010130 | NUMINOS® M , reflector, copper   |

|                       |         |
|-----------------------|---------|
| Gross weight          | 0.45 kg |
| Shape of cut-out      | round   |
| Installation depth    | 10 cm   |
| Installation diameter | 12 cm   |