


## PANEL P

### 1200/600 60 830 WB UGR19 ML DALI WH

The PANEL P product family stands for high energy savings, easy installation and long-lasting quality. Available in three sizes, the panels are ideal for offices, schools, health centres or retail spaces. With an efficiency of up to 200 lm/W, the lights make a significant contribution to reducing energy consumption. Thanks to UGR<19, they are ideal for screen-based workstations and provide glare-free light that is easy on the eyes. Available with ON/OFF or DALI control and in 3000K or 4000K light colours, they offer maximum design flexibility. Integrated through-wiring and external ballast allow quick, tool-free installation - ideal for time-critical projects.



## TECHNICAL DATA

Item no.	1010120
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	600-950 mA
Wattage	26 W
Ambient temperature	80 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	29
Number of luminaires at LS C16A	48
Level of inrush current	14.75 A
Duration of inrush current	256 µs
Lumen	4635 / 7248 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	white
CRI	80
Binning	3 SDCM
Service life	100000 h
Risk Group	1
Length	119.5 cm

## Light Source

2385581		<b>Width</b>	59.5 cm
		<b>Height</b>	3.6 cm
		<b>Net weight</b>	3.6 kg
		<b>Gross weight</b>	3.9 kg