


## SIGHT EVO

3~ spot, single, rectangular, 4000 K, 25 W, 60°, white / black

SIGHT EVO - the flexible 3-phase track spotlight series for perfect accent lighting. With single or double-flame spots, CCT options (3,000/4,000 K) and two total wattage options (18 W / 25 W), it provides the perfect setting for shops, galleries or showrooms. With UGR<19 and CRI>90, SIGHT EVO impresses with first-class light quality. The DALI option and uncomplicated installation make these lights perfect for versatile applications.



## TECHNICAL DATA

Item no.	1010149
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	25 W
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	15
Number of luminaires at LS C16A	24
Level of inrush current	65 A
Duration of inrush current	200 µs
Lumen	3200 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white/black
CRI	90
UGR ≤	16
Service life	50000 h
Risk Group	1

## Light Source



<b>Length</b>	117.5 cm
<b>Width</b>	4.1 cm
<b>Height</b>	4 cm
<b>Net weight</b>	0.82 kg
<b>Gross weight</b>	1.3 kg