



## HELIA PRO S

Wall-mounted light, single, DALI, P2, cylindrical, 2700 K, 6W, 24°, anthracite

The HELIA PRO wall light range offers flexible solutions for accentuating façades with two housing sizes and two wattage classes, either as single or up/down lighting. Efficient LED technology, DALI control, precise light distribution and resistance to sea air enable high-quality architectural lighting in outdoor areas.

### TECHNICAL DATA

Item no.	1010165
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	150 mA
Safety class	I
Wattage	6 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	15
Number of luminaires at LS C16A	24
Level of inrush current	65 A
Duration of inrush current	200 µs
Temperature at glass (light emission)	55 °C
Lumen	600 lm

## Light Source

1028936	
---------	---

<b>Colour temperature</b>	2700 Kelvin
<b>Beam angle</b>	24 °
<b>Color</b>	anthracite
<b>CRI</b>	80
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Height</b>	17.5 cm
<b>Depth</b>	10 cm
<b>Diameter</b>	6.5 cm
<b>Net weight</b>	0.77 kg
<b>Gross weight</b>	0.98 kg