



HELIA PRO S

Wall-mounted light, up/down, DALI, P2, cylindrical, 2700 K, 12W, 24°, white

The HELIA PRO wall light range offers flexible solutions for accentuating façades with two housing sizes and two wattage classes, either as single or up/down lighting. Efficient LED technology, DALI control, precise light distribution and resistance to sea air enable high-quality architectural lighting in outdoor areas.

TECHNICAL DATA

| | |
|---------------------------------------|--------------------|
| Item no. | 1010168 |
| Number of different light outlets | 2 |
| IP Code | IP65 |
| Impact resistance class | IK 06 |
| Impact resistance | 1 Joule |
| Assembly | Surface |
| Assembly details | Wall |
| Dimmable | Yes |
| Dimming technology | DALI 2 |
| Number of through-wires | 15 |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 300 mA |
| Safety class | I |
| Wattage | 12 W |
| Ambient temperature | 80 °C |
| Minimum ambient temperature | -25 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 15 |
| Number of luminaires at LS C16A | 24 |
| Level of inrush current | 65 A |
| Duration of inrush current | 200 µs |
| Temperature at glass (light emission) | 55 °C |

Light Source

| | |
|---------|---|
| 1028936 |  |
|---------|---|

| | |
|---------------------------|-------------|
| Lumen | 1200 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 24 ° |
| Color | white |
| CRI | 80 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 17.5 cm |
| Depth | 10 cm |
| Diameter | 6.5 cm |
| Net weight | 0.87 kg |
| Gross weight | 1.08 kg |