



## HELIA PRO L

Wall-mounted light, single, DALI, P2, cylindrical, 2700 K, 15W, 24°, anthracite

The HELIA PRO wall light range offers flexible solutions for accentuating façades with two housing sizes and two wattage classes, either as single or up/down lighting. Efficient LED technology, DALI control, precise light distribution and resistance to sea air enable high-quality architectural lighting in outdoor areas.

### TECHNICAL DATA

Item no.	1010173
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	380 mA
Safety class	I
Wattage	15 W
Ambient temperature	80 °C
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	15
Number of luminaires at LS C16A	24
Level of inrush current	65 A
Duration of inrush current	200 µs
Temperature at glass (light emission)	55 °C

## Light Source



<b>Lumen</b>	1800 lm
<b>Colour temperature</b>	2700 Kelvin
<b>Beam angle</b>	24 °
<b>Color</b>	anthracite
<b>CRI</b>	80
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Height</b>	30.5 cm
<b>Depth</b>	15.5 cm
<b>Diameter</b>	10.8 cm
<b>Net weight</b>	1.62 kg
<b>Gross weight</b>	2.2 kg