



## HELIA PRO L

Wall-mounted light, up/down, DALI, P2, 2700 K, 30W, Touch, 24°, anthracite

The HELIA PRO wall light range offers flexible solutions for accentuating façades with two housing sizes and two wattage classes, either as single or up/down lighting. Efficient LED technology, DALI control, precise light distribution and resistance to sea air enable high-quality architectural lighting in outdoor areas.

### TECHNICAL DATA

|                                       |                    |
|---------------------------------------|--------------------|
| Item no.                              | 1010175            |
| Number of different light outlets     | 2                  |
| IP Code                               | IP65               |
| Impact resistance class               | IK 08              |
| Impact resistance                     | 5 Joule            |
| Assembly                              | Surface            |
| Assembly details                      | Wall               |
| Dimmable                              | Yes                |
| Dimming technology                    | DALI 2, Touch      |
| Number of through-wires               | 28                 |
| Primary nominal voltage               | 220-240V ~50/60 Hz |
| Secondary power / voltage             | 800 mA             |
| Safety class                          | I                  |
| Wattage                               | 30 W               |
| Ambient temperature                   | 80 °C              |
| Minimum ambient temperature           | -20 °C             |
| Maximum ambient temperature           | 45 °C              |
| Number of luminaires at LS B16A       | 28                 |
| Number of luminaires at LS C16A       | 42                 |
| Level of inrush current               | 30 A               |
| Duration of inrush current            | 100 µs             |
| Temperature at glass (light emission) | 60 °C              |

## Light Source

|  |                                                                                   |
|--|-----------------------------------------------------------------------------------|
|  |  |
|--|-----------------------------------------------------------------------------------|

|                           |             |
|---------------------------|-------------|
| <b>Lumen</b>              | 3600 lm     |
| <b>Colour temperature</b> | 2700 Kelvin |
| <b>Beam angle</b>         | 24 °        |
| <b>Color</b>              | anthracite  |
| <b>CRI</b>                | 80          |
| <b>Service life</b>       | 50000 h     |
| <b>Risk Group</b>         | 1           |
| <b>Height</b>             | 30.5 cm     |
| <b>Depth</b>              | 15.5 cm     |
| <b>Diameter</b>           | 10.8 cm     |
| <b>Net weight</b>         | 1.91 kg     |
| <b>Gross weight</b>       | 2.5 kg      |