



48V SYSTEM

Intrack LED driver, 48VDC, 100 W, incl. 300 cm connection cable for 220-240VAC and DALI through-wiring, black

Maximum minimalism and simple elegance: with an output of up to 100 watts, the LED driver is designed for flexible use in the 48V TRACK mounting tracks. Thanks to the four-wire 220V-240V / DALI through-wiring, controllable lighting concepts with particularly small tracks and spot-lights are easy to realise. The 3-metre cable supplied offers additional flexibility - ideal if the 48V rails are to be suspended.

TECHNICAL DATA

Item no.	1010446
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Ceiling, Wall
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	48 V
Safety class	II
Safety class	II
Wattage	115 W
Ambient temperature	75 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	16
Number of luminaires at LS C16A	26
Level of inrush current	60 A
Duration of inrush current	200 µs
Color	black
Length	29.75 cm
Width	1.6 cm
Height	1.9 cm
Net weight	0.332 kg

Gross weight	0.36 kg
--------------	---------