

BATTEN FLAT P

1200 52 830/840/850 ML DALI2 EM 3H WH

BATTEN FLAT P - the robust IP44 solution for multi-storey car parks, corridors/hallways or plant rooms. The multi-lumen and multi-CCT function (3,000/4,000/5,000 K) allows the light output to be flexibly adjusted. Variants with DALI2 control or integrated HF motion sensor automatically activate the light only when there is movement, thus enabling energy-saving, intelligent operation. The end caps, which can be opened without tools, simplify maintenance and installation.

TECHNICAL DATA

Item no.	1010913
IP Code	IP44
Impact resistance class	IK 04
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	200-350 mA
Safety class	I
Wattage	20 W
Ambient temperature	80 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	43
Number of luminaires at LS C16A	71
Lumen	2609 / 4720 lm
Beam angle	120 °
Color	white
CRI	80
UGR ≤	25
Risk Group	1

Length	120 cm
Width	15.2 cm
Height	5.2 cm
Net weight	3.75 kg
Gross weight	4.14 kg

Accessories

1010932	BATTEN FLAT P , Suspension kits with 2m 2pcs
1010934	
1010931	BATTEN FLAT P , Wall brackets, 2pcs
1010933	BATTEN FLAT P , Horizontal cable wire suspension kits, 2pcs