

## NUMINOS® MOVE S

white / chrome recessed ceiling light, 2700K 20°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. This also includes NUMINOS® MOVE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS® from SLV?

### TECHNICAL DATA

Item no.:	1005330
Number of different light outlets	1
Secondary power / secondary voltage	250mA
Height	6.35 cm
Diameter	10.0 cm
Installation diameter	9.0 cm
Installation depth	8.5 cm
Net weight	0.19 kg
Gross weight	0.203 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Lumen	690 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50

## Accessories

Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C

1004055	LED driver , 6.5-10W 250mA PHASE
1004058	LED driver , 6.5-10W 250mA
1004067	LED driver , 15W 250mA DALI
1004786	NUMINOS® S , diffuser Ellipse
1004787	NUMINOS® S , diffuser Prisma
1004788	NUMINOS® S , diffuser Frosted
1004789	NUMINOS® S , diffuser Wabe

## Notes

---

---

---

---

---