## **NUMINOS® MOVES**

white / chrome recessed ceiling light, 2700K  $40^{\circ}$ 

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® MOVE S recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## **TECHNICAL DATA**

| Item no.:                           | 1005333     |
|-------------------------------------|-------------|
| Number of different light outlets   | 1           |
| Secondary power / secondary voltage | 250mA       |
| Height                              | 6.35 cm     |
| Diameter                            | 10.0 cm     |
| Installation diameter               | 9.0 cm      |
| Installation depth                  | 8.5 cm      |
| Net weight                          | 0.19 kg     |
| Gross weight                        | 0.203 kg    |
| IP Code                             | IP 20       |
| Safety class                        | III         |
| Impact resistance class             | IK02        |
| Impact resistance                   | 0,2 Joule   |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Lumen                               | 690 lm      |
| Colour temperature                  | 2700 Kelvin |
| Beam angle                          | 40 °        |
| Color                               | white       |
| CRI                                 | 90          |
| UGR≤                                | 19          |
| LXXBXX data                         | L80B50      |
|                                     | •           |



## **Accessories**

| 1004055 | LED driver , 6.5-10W 250mA PHASE |
|---------|----------------------------------|
| 1004058 | LED driver , 6.5-10W 250mA       |
| 1004067 | LED driver , 15W 250mA DALI      |
| 1004786 | NUMINOS® S , diffuser Ellipse    |
| 1004787 | NUMINOS® S , diffuser Prisma     |
| 1004788 | NUMINOS® S , diffuser Frosted    |
| 1004789 | NUMINOS® S , diffuser Wabe       |

| Minimum ambient temperature | -20 °C |
|-----------------------------|--------|
| Maximum ambient temperature | 40 °C  |

| Notes |  |  |  |
|-------|--|--|--|
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |
|       |  |  |  |