

NUMINOS® MOVE S

black recessed ceiling light, 3000K 55°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE S recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.:	1005343
Number of different light outlets	1
Secondary power / secondary voltage	250mA
Height	6.35 cm
Diameter	10.0 cm
Installation diameter	9.0 cm
Installation depth	8.5 cm
Net weight	0.19 kg
Gross weight	0.203 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Lumen	690 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50

Accessories

Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C

1004055	LED driver , 6.5-10W 250mA PHASE
1004058	LED driver , 6.5-10W 250mA
1004067	LED driver , 15W 250mA DALI
1004786	NUMINOS® S , diffuser Ellipse
1004787	NUMINOS® S , diffuser Prisma
1004788	NUMINOS® S , diffuser Frosted
1004789	NUMINOS® S , diffuser Wabe

Notes
