

NUMINOS® MOVE S

white / chrome recessed ceiling light, 3000K 55°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® MOVE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 1005354 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 250mA |
| Height | 6.35 cm |
| Diameter | 10.0 cm |
| Installation diameter | 9.0 cm |
| Installation depth | 8.5 cm |
| Net weight | 0.19 kg |
| Gross weight | 0.203 kg |
| IP Code | IP 20 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Lumen | 700 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |

Accessories

| | |
|-----------------------------|--------|
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |

| | |
|---------|----------------------------------|
| 1004055 | LED driver , 6.5-10W 250mA PHASE |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004789 | NUMINOS® S , diffuser Wabe |

Notes
