

## **WORKLIGHT**

white free-standing lamp. 79W 4000K  $80^{\circ}$ 

As a consistent further development of our WORKLIGHT series, this WORKLIGHT is an office free-standing light for VDU workstations, equipped with state-of-the-art technology and highly efficient, high-output LEDs and, of course, UGR  $\leq$  19. Equipped with a motion sensor, the built-in daylight control and the possibility of dimming, it meets all the requirements of today's office lighting. The WORK-LIGHT is ready for direct connection to a 230V mains power supply thanks to its pre-installed driver and supply cable including plug. This light contains integrated LED light bulbs.

## **TECHNICAL DATA**

Item no.:	1005391
Number of different light outlets	2
Primary nominal voltage	200-240V ~50/60Hz mA/V
Secondary power / secondary voltage	2000mA
Length	69.2 cm
Width	31.0 cm
Height	195.0 cm
Net weight	17.1 kg
Gross weight	18.297 kg
IP Code	IP 20
Safety class	I
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Mobile
Wattage	79 W
Lumen	7600 lm
Colour temperature	4000 Kelvin
Beam angle	80 °
Color	white
CRI	80
UGR≤	19
LXXBXX data	L80B10

1005001

					-				4			-		-		-	ч.	-	-	-	4	ч,	ч.	ч.	4									
	4	4	3.3	u	J	J.	a,	a,	J	J	J	J	J	ä	ä	ä	a,																	
1.	. L L	. L L	ננו	J	J	J	a,	a,	J.	J	4	J	J	J	4		4			1		ı		1	4	1	1	4	1	1	J.	1	1	1
											- 1	- 6	- 1																					



Minimum ambient temperature	-20 °C						
Maximum ambient temperature	45 °C						

Notes			