MILANDOS 6

black recessed ceiling light, 3000K 45°

Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. The long LED lifespan of 60,000 hours and the high colour reproduction index of over 90 are also convincing across the board. With a UGR of 16, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends seamlessly into any room. The spotlight is also quick and easy to install. Experience MILANDOS in action and convince yourself of a successful lighting experience.

TECHNICAL DATA

Item no.:	1005416
Secondary power / secondary volta- ge	700mA
Length	19.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	19.0 cm
Installation width	4.9 cm
Installation depth	7.0 cm
Net weight	0.3 kg
Gross weight	0.321 kg
IP Code	IP 20
Safety class	III
Safety class Impact resistance class	III IK02
Impact resistance class	IK02
Impact resistance class Assembly	IK02 Recessed
Impact resistance class Assembly Assembly details	IK02 Recessed Ceiling
Impact resistance class Assembly Assembly details Lumen	IK02 Recessed Ceiling 780 Im
Impact resistance class Assembly Assembly details Lumen Colour temperature	IK02 Recessed Ceiling 780 Im 3000 Kelvin
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle	IK02 Recessed Ceiling 780 Im 3000 Kelvin 45 °
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle Color	IK02 Recessed Ceiling 780 Im 3000 Kelvin 45 ° black
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle Color CRI	IK02 Recessed Ceiling 780 Im 3000 Kelvin 45 ° black





Ambient temperature	30 °C

Accessories

1002423	LED driver MEDO 300 dimmable DALI- /1-10V
464147	LED Driver 14.7W 700mA dimmable

Notes			