

MILANDOS 8

white recessed ceiling light, 3000K 45°

Minimalist, compact and innovative, the MILANDOS recessed ceiling light convinces with its lighting properties. The long LED lifespan of 60,000 hours and the high colour reproduction index of over 90 are also convincing across the board. With a UGR of 23, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. The spotlight is also quick and easy to install. Experience MILANDOS in action and convince yourself of a successful lighting experience.

TECHNICAL DATA

Item no.:	1005426
Secondary power / secondary voltage	700mA
Length	25.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	25.0 cm
Installation width	4.9 cm
Installation depth	7.0 cm
Net weight	0.4 kg
Gross weight	0.428 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling
Lumen	1300 lm
Colour temperature	3000 Kelvin
Beam angle	45 °
Color	white
CRI	90
UGR ≤	23
LXXBXX data	L80B50

Ambient temperature

30 °C

Accessories

1002423	LED driver MEDO 300 dimmable DALI- /1-10V
1006202	LED Driver , 20W 700mA

Notes
