

## NUMINOS® XS

black / white recessed ceiling light, 4000K 40°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® XS recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

### TECHNICAL DATA

|                                     |               |
|-------------------------------------|---------------|
| Item no.:                           | 1005539       |
| Secondary power / secondary voltage | 200mA         |
| Height                              | 4.5 cm        |
| Diameter                            | 6.5 cm        |
| Installation diameter               | 5.5 cm        |
| Installation depth                  | 11.0 cm       |
| Net weight                          | 0.09 kg       |
| Gross weight                        | 0.096 kg      |
| IP Code                             | IP 20 / IP 44 |
| Safety class                        | III           |
| Impact resistance class             | IK02          |
| Impact resistance                   | 0,2 Joule     |
| Assembly                            | Recessed      |
| Assembly details                    | Ceiling       |
| Lumen                               | 730 lm        |
| Colour temperature                  | 4000 Kelvin   |
| Beam angle                          | 40 °          |
| Color                               | black         |
| CRI                                 | 90            |
| UGR ≤                               | 22            |
| LXXBXX data                         | L80B50        |
| Minimum ambient temperature         | -20 °C        |

|                             |       |
|-----------------------------|-------|
| Maximum ambient temperature | 40 °C |
|-----------------------------|-------|

Accessories

|         |                                                         |
|---------|---------------------------------------------------------|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector           |
| 1005610 | LED Driver , 200mA 10W, Quick Connector                 |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser                                  |
| 1005613 | NUMINOS® XS , transparent diffuser                      |
| 1005614 | NUMINOS® XS , frosted diffuser                          |
| 1005615 | NUMINOS® XS , black diffuser                            |

Notes

---

---

---

---

---