NUMINOS® MOVE XS

black recessed ceiling light, 3000K 55°

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® MOVE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| Item no.: | 1005577 |
|--|-------------|
| Secondary power / secondary volta- ge | 200mA |
| Height | 5.5 cm |
| Diameter | 8.0 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 11.0 cm |
| Net weight | 0.11 kg |
| Gross weight | 0.118 kg |
| IP Code | IP 20 |
| Safety class | 111 |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Lumen | 690 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 25 |
| LXXBXX data | L80B50 |
| Minimum ambient temperature | -20 °C |
| | |





Maximum ambient temperature

40 °C

Accessories

| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
|---------|--|
| 1005610 | LED Driver , 200mA 10W, Quick Connec- tor |
| 1005611 | LED Driver , 200mA 13,5W DALI dimma- ble, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1005615 | NUMINOS® XS , black diffuser |

Notes