NUMINOS® MOVE XS

black recessed ceiling light, 4000K 55°

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE XS recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?

TECHNICAL DATA

Item no.:	1005595
Secondary power / secondary volta- ge	200mA
Height	5.5 cm
Diameter	8.0 cm
Installation diameter	6.8 cm
Installation depth	11.0 cm
Net weight	0.11 kg
Gross weight	0.118 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Lumen	710 lm
Colour temperature	4000 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR≤	25
LXXBXX data	L80B50
Minimum ambient temperature	-20 °C





Maximum ambient temperature	40 °C

Accessories

1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005610	LED Driver , 200mA 10W, Quick Connector
1005611	LED Driver , 200mA 13,5W DALI dimma- ble, Quick Connector
1005612	NUMINOS® XS , diffuser
1005613	NUMINOS® XS , transparent diffuser
1005614	NUMINOS® XS , frosted diffuser
1005615	NUMINOS® XS , black diffuser

Notes			