NUMINOS® XL PHASE

white / black pendant light, 36W 3000K 36°

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® XL PHASE pendant light, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The pendant light can convince with a power consumption of 36 watts, luminous flux of 3490 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.:	1005715
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary volta- ge	900mA
Pendant length	250.0 cm
Height	25.8 cm
Diameter	12.0 cm
Net weight	1.745 kg
Gross weight	1.867 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	36 W
Lumen	3490 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR≤	19

							4				4			4		4		4	ч	ч	ч	4	7	ч	4	ч	4								
	4	- 4		a.	ă,	J.	J.	J	4	J	4	J	J	J	J,	a,	a,	J.	ä																
ı,	L	1	ı	J	1	J	J	J	J	ä	J	J	J	J	ä	J	ä		a,			J		J.		1	J.	ı	J.	J.	J,	١,	1	u	4
					ă.			а		а		a.	a.	a.	a.	а	a.	J.	J.	a.	a.	a.	a.	ı	ı	ă.	a.	ă.							



Accessories

1006170	NUMINOS® XL , white front ring
---------	--------------------------------
