

## **NUMINOS® XL PHASE**

black pendant light, 36W 4000K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® XL PHASE, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 36 watts, luminous flux of 3760 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

## **TECHNICAL DATA**

Item no.:	1005718
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	900mA
Pendant length	250.0 cm
Height	25.8 cm
Diameter	12.0 cm
Net weight	1.745 kg
Gross weight	1.867 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	36 W
Lumen	3760 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR≤	19

							4				4			4		4		4	ч	ч	ч	4	ч	ч	ч	ч	4								
	4	- 4		a.	ă,	J.	J.	J	4	J	4	J	J	J.	J,	a,	ä	J.	ä																
ı,	L	1 1	ı	J	1	J	J	J	J	J.	J	J	a,	J.	ä	J	J		a,			J		J.		1	J.	ı	J.	ı	J,	١,	L	J	J.
					ă.			а		а		a.	a.		a.	а	a.	J.	J.	a.	a.	a.	a.	ı	ı	ă.	a.	ы							



## Accessories

1006170	NUMINOS® XL , white front ring
---------	--------------------------------
