

NUMINOS® GIMBLE M

black recessed ceiling light, 4000K 55°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® GIMBLE M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.:	1005963
Number of different light outlets	1
Secondary power / secondary voltage	500mA
Height	9.5 cm
Diameter	13.5 cm
Installation diameter	12.0 cm
Installation depth	9.5 cm
Net weight	0.42 kg
Gross weight	0.449 kg
Safety class	Ш
Accomply	December
Assembly	Recessed
Assembly details	Ceiling
Assembly details	Ceiling
Assembly details Lumen	Ceiling 1600 lm
Assembly details Lumen Colour temperature	Ceiling 1600 lm 4000 Kelvin
Assembly details Lumen Colour temperature Beam angle	Ceiling 1600 lm 4000 Kelvin 55 °
Assembly details Lumen Colour temperature Beam angle Color	Ceiling 1600 lm 4000 Kelvin 55 ° black



Accessories

1004054	LED driver , 30W 500mA PHASE
1004064	LED driver , 21-29.5W 500/600/700mA
1004069	LED driver , 1.5-40,6W 230/350/500/700mA
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma
1004792	NUMINOS® M , diffuser Frosted
1004793	NUMINOS® M , diffuser Wabe

Notes			