## **NUMINOS® GIMBLE L**

black recessed ceiling light, 3000K  $55^{\circ}$ 

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## **TECHNICAL DATA**

Item no.:	1005999
Number of different light outlets	1
Secondary power / secondary voltage	700mA
Height	11.5 cm
Diameter	16.0 cm
Installation diameter	14.5 cm
Installation depth	11.5 cm
Net weight	0.6 kg
Gross weight	0.642 kg
Safety class	III
Assembly	Recessed
Assembly details	Recessed Ceiling
Assembly details	Ceiling
Assembly details  Lumen	Ceiling 2150 lm
Assembly details  Lumen  Colour temperature	Ceiling 2150 lm 3000 Kelvin
Assembly details  Lumen  Colour temperature  Beam angle	Ceiling 2150 lm 3000 Kelvin 55 °
Assembly details  Lumen  Colour temperature  Beam angle  Color	Ceiling 2150 lm 3000 Kelvin 55 ° black



## **Accessories**

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe

Notes			